

COELAN[®] - THINNER FOR BOAT COATINGS

PRODUCT DESCRIPTION	
Features	Liquid thinner on the basis of an organic solvent mixture.
Colour	Transparent
Packing units	250-ml-bottles 1-litre-bottles 5-litre-cans
Characteristics	Ready-to-use thinner and cleaner.
Field of application	For the cleaning of tools and equipment and for application purposes. Also suitable as thinner for our COELAN [®] -BOAT COATING. Please refer to the corresponding TDS and our GUIDE TO BOAT COATING.
Storage	Min. 12 months in dosed original-containers stored in a dry place at temperatures between + 5 ° C and + 25 ° C. Direct sunlight is to be avoided. 24 hours before application, the material should be acclimated at temperatures between + 18 ° C and + 20 ° C. Opened containers have to be sealed off air tightly and firmly and should be used up as soon as possible.
PRODUCT DATA	
Density	Approx. 0,87 g/cm ³
Consumption	Depending on the targeted application. For details please refer to our GUIDE TO BOAT COATING.
APPLICATION INSTRUCTIONS	
Application	The cleaning of tools and equipment has to take place as long as the contamination caused by the EP or PU resins are still wet. For details please refer to our GUIDE TO BOAT COATING.
Working temperature	Temperature of material, air and substrate must be min. + 5 ° C and max. + 30 ° C. Relative air-humidity < 85 %. The temperature of the substrate should be at least 3 ° C above dew point.
IMPORTANT INFORMATION	
Danger information, danger classes, measures of precaution and information for disposal as per Safety Data Sheet.	

COELAN[®]-THINNER FOR BOAT COATINGS

ISSUE: 12/01

To the best of our knowledge, the technical information contained on this product information is reliable. As the product may be used in conditions which we cannot foresee, this advice is not legally binding. Furthermore, we reserve the right to make technical changes in line with progress. On publication of revised special instructions for use, any existing technical information shall be invalid. For any queries, you may contact our special technical advice service. Agreements and warranties must in principle be in writing. Verbal agreements should therefore be confirmed in writing. In addition, our terms of delivery and payment apply.