

## COELAN<sup>®</sup> RETARDATION AGENT-T

<b>PRODUCT DESCRIPTION</b>	
<b>Features</b>	Organic solvent mixture with special additives.
<b>Packing units</b>	1-l hopper bottles
<b>Characteristics</b>	Prolongs the skin-formation of the air-humidity drying polyurethane resins.
<b>Field of application</b>	Additive to polyurethane resins to prolong the skin-formation time. To be added under operating conditions with very high air humidity >85% and very high temperatures >30°C.
<b>Storage</b>	Min. 12 months in closed original containers at a dry place at temperatures between +5°C and +25°C. Avoid direct sunlight and frost! 24 hours before application the material should be acclimated at temperatures between +18°C and +20°C.
<b>PRODUCT DATA</b>	
<b>Density</b>	Approx. 0,87 g/cm <sup>3</sup>
<b>Consumption</b>	Addition of approx. 1-3% by weight.
<b>APPLICATION INSTRUCTIONS</b>	
<b>Application</b>	To be mixed evenly, homogeneously and without streaks with the prepared quantity of polyurethane resin by means of a low running agitator (max. 300 turns/minute) or a stirring staff.
<b>IMPORTANT INFORMATION</b>	
Danger information, danger classes, measures of precaution and information for disposal as per Safety Data Sheet.	